

			
<b>Model</b>	<b>GODOX SL150 II</b>	<b>GODOX VL150</b>	<b>GODOX UL200</b>
<b>Max. Power Output</b>	150W		
<b>CRI</b>	96		
<b>TLCI</b>	97	95	97
<b>Colour Temperature</b>	5600K ± 200K		
<b>Cooling System</b>	Fan	Quiet Fan	Passive (No Fan)
<b>Dimming</b>	Yes - 0 to 100%		
<b>Brightness (with High-Performance Reflector)</b>	58,000 lux at 1m	61,000 lux at 1m	58,000 lux at 1m
<b>Dual Power</b>	AC Adapter Only	AC Adapter or V-Lock Battery (Sold Separately)	
<b>Operating Temperature</b>	-10°C to 40°C		
<b>Wireless Control</b>	32 channels / 6 Groups	16 channels / 6 Groups	16 channels / 6 Groups
<b>Material</b>	Metal		
<b>Yoke</b>	Swivel 360°		
<b>Fitting</b>	Bowens S Fitting		
<b>Fixture Dimensions</b>	34 x 20 x 16 cm	30x 18x 14 cm	31.7x 21.8 x 17 cm
<b>Fixture Weight</b>	2.95 kg	1.97 kg	3.1 kg
<b>Controller Block Dimensions</b>		11.5 x 21.0 x 3.6 cm	11.5 x 38.0 x 3.6 cm
<b>Controller Block Weight</b>	N/A	0.86kg	0.86kg
<b>AC power input</b>	110 - 240V , 50 / 60 Hz		
<b>DC power input</b>	N/A	16.8V at 10 A	
<b>Battery Plate</b>	N/A	1x V-Mount	